

Klassic - LTKL 30



Self bunded 110% double wall design with

- Fluid level dipstick for tank and interstitial space
- Vent pipe for tank and interstitial space
- Suction foot valve, overfill protection and electronic overfill alarm
- Corner container lock castings for ease of transport
- Access manway
- Warranty - 5 years structural, 1 year on valves (conditions apply)

Pump bay model standard with:

- Bunded pump bay with lockable weatherproof doors
- Galvanised access ladder and platform; with ladder fitted to either side of the platform (ex-factory)
- Galvanised kick plate and middle rail provided for additional safety of users


Specifications

Description

Capacity SFL, litres	28,750 (USG - 7,596, IG - 6,324)
Capacity GFL, litres	30,471 (USG - 8,050, IG - 6,703)
Length, mm	6,058 (20 ft)
Width, mm	2,438 (8 ft)
Height, mm	2,896 (9.5 ft)
Tare Weight, Kg	8,300**
Compliance	AS1940, AS1692, S1657, UL142, ULCS601, ***BS799-5

** Tank weights are approximate

*** BS799-5 available upon request



Disclaimer: Information and photographs shown are for marketing purposes only. Actual product may vary to images shown due to continual improvement processes, design changes and optional extras

AUSTRALIA
+61 3 9775 1366
FUELCO.COM.AU

AFRICA
+27 (016) 421 8043
FUELCO-SA.COM

MENA
+ 971 4 232 4985
FUELCO.AE