

Klassic - LTKL 68



Self bunded double wall design with

- Fluid level dipstick for tank and interstitial space
- Vent pipe for tank and interstitial space
- Suction foot valve, overfill protection and electronic overfill alarm
- Corner container lock castings for ease of transport
- Access manway
- Warranty - 5 years structural, 1 year on valves (conditions apply)

Pump bay model standard with:

- Bunded pump bay with lockable weatherproof doors
- Galvanised access ladder and platform; with ladder fitted to either side of the platform (ex-factory)
- Galvanised kick plate and middle rail provided for additional safety of users

Specifications

Description

Capacity SFL, litres 64,600 (USG - 17,067, IG - 14,210)

Capacity GFL, litres 68,036 (USG - 17,975, IG - 14,966)

Length, mm 12,192 (40 ft)

Width, mm 2,438 (8 ft)


Height, mm 2,896 (9.5 ft)

Tare Weight, Kg 14,600**

Compliance AS1940, AS1692, S1657, UL142, ULCS601, ***BS799-5

** Tank weights are approximate

*** BS799-5 available upon request



Disclaimer: Information and photographs shown are for marketing purposes only. Actual product may vary to images shown due to continual improvement processes, design changes and optional extras

AUSTRALIA

+61 3 9775 1366
FUELCO.COM.AU

AFRICA

+27 (016) 421 8043
FUELCO-SA.COM

MENA

+ 971 4 232 4985
FUELCO.AE